




**2006-2007 GSXR600 Z-Fi INSTALLATION INSTRUCTIONS**  
**P/N 127008**

**WARNING!**

**USE ONLY IN RACE OR OTHER CLOSED COURSE APPLICATIONS AND NEVER ON PUBLIC ROADS**

Z-Fi products do not meet California CARB highway requirements

**Z-Fi CONTROL UNIT**  
**FUEL HARNESS**  
**DOWNLOAD Z-Fi MAPPER SOFTWARE & ITS INSTRUCTIONS FROM WEBSITE**  
**USB CABLE**  
**SCOTCHLOK**  
**SWINGARM STICKERS**



- (1) MAP SELECT**
- (2) ZAFM CONNECTORS**
- (3) SWITCHED POWER (RED TAG)**
- (4) LOWER INJECTORS (YELLOW TAG)**
- (5) UPPER INJECTORS**
- (6) GEAR POSITION**
- (7) THROTTLE POSITION SENSOR**
- (8) CRANK POSITION**
- (9) GROUND LUG**

**WE STRONGLY SUGGEST THAT AN EXPERIENCED TECHNICIAN  
INSTALL THIS BAZZAZ PRODUCT**

1. Place the Z-Fi control unit in the tail section of the bike.
2. Route the fuel harness on the left hand side of the bike.
3. Plug the Z-Fi harness in-line with the lower injectors (yellow tag on harness is CYL # 1 lower injector).

**WARNING! Make sure that the Z-Fi harness injector male pins make proper contact with the stock harness injector connectors.**

4. Plug the Z-Fi harness in-line with the upper injectors (photo 1).




Photo 1

**WARNING! Make sure that the Z-Fi harness injector male pins make proper contact with the stock harness injector connectors.**

5. Plug the Z-Fi harness in-line with the primary/lower throttle position sensor and stock harness TPS connector (photo 2).






Photo 2

6. Plug the Z-Fi harness in-line with the stock Crank Position Sensor connectors (photo 3).



7. Plug the Z-Fi harness in-line with the Gear Position Sensor (photo 4).




8. Attach the ground lug from the Z-Fi to the crankcase using one of the 8mm crankcase bolts.


9. Locate the orange/white wire on the diagnostics connector located behind the battery. Use the supplied scotchlok to tap into this wire. Insert the switched power (red tag) T-Tap into the scotchlok.

**WARNING! Proper alignment of the T-TAP terminal with the scotchlok is critical for proper operation**

The Bazzaz Z-Fi controller is capable of storing two maps. These maps can be selected through the use of a map select switch which can be mounted on the handlebar for easy access and can be purchased separately. Or these maps can be selected by connecting or disconnecting the map select jumper supplied with kit. When the map select jumper is connected the control unit is operating using **Map 1** and when the map select jumper is disconnected the control unit is operating using **Map 2**. **Upon installing the system connect it to the control unit using the software and verify you have selected the proper map to correspond with your model year.**



**Map 1**



**Map 2**

**\* To create the ideal map(s) we recommend using the optional Z-AFM self-tuning module. \***