



Kawasaki ZX14R 2012-2013

Z-Fi Installation Instructions Part # F445



Parts List:

Z-Fi Control Unit

Fuel Harness

Scotchlok (3)

Cable Ties

Velcro

USB Cable

Swingarm Stickers

Download Z-Fi Mapper Software at bazzaz.net


Software instructions available at bazzaz.net

USE ONLY IN RACE OR OTHER CLOSED COURSE APPLICATIONS AND NEVER ON PUBLIC ROADS

Z-Fi products are not certified by the California Air Resource Board (CARB) for use on CA highways

Contact Bazzaz tech support at 909-597-8300 for questions

BAZZAZ HARNESS CONNECTOR IDENTIFICATION




FUEL HARNESS

Read through all instructions before beginning installation. This is not a replacement for the ECU. This document is intended for use by qualified technicians. Refer to a factory service manual for more specific stock component identification and location information.

WE STRONGLY SUGGEST THAT AN EXPERIENCED TECHNICIAN INSTALL THIS BAZZAZ PRODUCT

1. Begin the installation by removing the rider seat, tank and side panels.
2. Place the **CONTROL UNIT** in the left, front fairing, securing it with the provided Velcro. Plug the main connector of the Bazzaz **FUEL HARNESS** into the control unit.

Bazzaz control unit




3. Begin to route the fuel harness back towards the engine, on the left side. Locate the factory **INJECTORS**, which can be found between the throttle bodies and the frame. From left to right disconnect the factory connectors from each injector. Plug the Bazzaz injector connectors in-line with each factory connector and injector. **Start with the Bazzaz # 1 injector connectors having the pink/white wires.**

Factory injector connector




Injector is behind factory connector in this photo




Bazzaz # 1 injector connectors




4. Begin to route the Bazzaz Throttle Position Sensor (TPS) connectors between the frame and throttle bodies to the right side of the bike. Locate the factory, black TPS and disconnect the connector from the sensor. Install the Bazzaz TPS connectors in-line between the factory connector and sensor.



5. Next, locate the factory Crank Position Sensor (CKPS) connectors which can be found towards the right side of the bike, slightly below the throttle bodies and between the frame and throttle bodies. Disconnect the factory CKPS connectors and install the Bazzaz CKPS connectors in-line with the factory connectors.




6. Locate the 4-pin, green, speed connector, which can be found on the left side of the motorcycle and behind the fairing. Trim the sheathing back of the 4-pin connector to expose the wiring. Crimp a supplied scotchlok onto the **green/red** wire and insert the Bazzaz SPEED connector (connector having pink wire) into the Scotchlok. You will be working on this 4-pin connector in step 5 as well.



7. Now, within the same 4-pin, green, speed connector, locate the exposed light green wire. Crimp a supplied scotchlok onto the **light green** wire and insert the Bazzaz **NEUTRAL** connector (connector having blue/white wire) into the Scotchlok.

Factory green, 4-pin connector




Bazzaz neutral connector

Scotchlok crimped onto the **light green** wire of the factory connector


8. Locate the common **GROUND** on the right side of the motorcycle and begin to route the Bazzaz ground lug between the frame and the throttle bodies. Attach the Bazzaz ground lug to the common ground.

Bazzaz ground



9. Next, locate the left side running light connector. Crimp a supplied Scotchlok onto the **red** wire of the factory connector and insert the Bazzaz **POWER** connector into the Scotchlok.

Factory running light connector



Bazzaz power connector

Scotchlok crimped onto the **red** wire of the factory connector


10. To complete the installation, use the supplied cable ties to secure the harnesses neatly along the routing path free of any moving or hot components (which could cause damage or failure of the system). If any problem is found, please carefully follow through the installation steps again. If problem still persists, please call **Bazzaz tech support at (909) 597-8300**. After it is determined that everything is correct, reinstall the components removed in step one and the installation will be complete.

The Bazzaz control unit is capable of storing two maps. These maps can be selected by connecting or disconnecting the map select jumper on the fuel harness (or you can switch maps on the fly with the handle bar mounted map select switch, sold separately). When the map select jumper is connected, the control unit is operating using map 1. When the map select jumper is disconnected, the control unit is operating using map 2.

The control unit is pre-programmed from the factory with an enhanced map in the map 1 position. The map 2 position is using the stock ECU map. You are able to load and unload maps as needed via the Z-Fi Mapper software.



Don't forget to download the Z-Fi Mapper software from bazzaz.net (under the software tab) so that you can adjust your fuel map. You will also need access to the Z-Fi Mapper software if you will be using the Z-AFM self-mapping kit.



Accessories you may be interested in to ENHANCE your Bazzaz experience

Z-AFM™ | Tuning Technology (for use with all Bazzaz fuel control units)

Quickly collect data to build ideal, self-made fuel maps while riding. [Part No. 127062]



Map Select Switch (for use with the Z-Fi, Z-Fi MX, Z-Fi QS and Z-Fi TC)

The Bazzaz Map Select Switch is a handlebar-mounted switch for convenient toggling between two maps held on the Bazzaz unit. For example, rider can toggle between a fuel efficient map, rain map, or a full power map. [Part No. 127078]

